

DIGITAL GLAZED VITRIFIED TILES



MADE IN INDIA

DIGITAL GLAZED VITRIFIED TILES



# DIGITAL GLAZED VITRIFIED TILES

## 60x120cm 600x1200mm

technology powered with **6COR** PRINTING | Random | Digital GVT/PGVT

CE | ISO 9001:2015

MADE IN INDIA



CE | ISO 9001:2015

MADE IN INDIA


DIGITAL GLAZED VITRIFIED TILES

DIGITAL GLAZED VITRIFIED TILES

NORMAL Size : 60cm x 120cm / 600x1200mm | Quantity : 2 Pcs. | Coverage Area : 1.44 Sq.Mtr.

**TILES LAYING INSTRUCTIONS**  
1. Before the start of the floor, ensure the floor is level and smooth. Check and complete the plastering and leveling at least two weeks prior to tiling.  
2. Before tiling, the floor must be thoroughly cleaned and made sure that they are completely free of dust, oil, grease, etc. It is also important to ensure that the floor is completely dry.  
3. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.  
4. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.  
5. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.  
6. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.  
7. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.  
8. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.  
9. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.  
10. The tiles should be laid on a surface that is completely flat and smooth. It is important to ensure that the floor is completely dry before tiling.

1. Use strong TDS on tiles, we recommend the use of strong bonding agent. Please follow the manufacturer's instructions for the same, with the correct amount of the use of TDS on tiles.  
2. It is important to ensure that the tiles are completely dry before tiling.  
3. It is important to ensure that the tiles are completely dry before tiling.  
4. It is important to ensure that the tiles are completely dry before tiling.  
5. It is important to ensure that the tiles are completely dry before tiling.  
6. It is important to ensure that the tiles are completely dry before tiling.  
7. It is important to ensure that the tiles are completely dry before tiling.  
8. It is important to ensure that the tiles are completely dry before tiling.  
9. It is important to ensure that the tiles are completely dry before tiling.  
10. It is important to ensure that the tiles are completely dry before tiling.



## DIGITAL GLAZED VITRIFIED TILES