



# TEXTURE

## NATURALE & LAPPATO

Cotton .....04

Sand .....08

Canvas .....12

Moka .....16

# TEXTURE



**“Un sorprendente gioco di riflessi. Suggestivo.”**

*Paul&Co*

**“A wonderful play of hues. Impressive.”**

**“Un surprenant jeu de reflets . Suggestif.”**

**“ Ein wundervolles Spiel von Reflexen. Bezaubernd”**

PAVIMENTO IN GRES PORCELLANATO SMALTATO, COLORATO IN MASSA, RETTIFICATO  
GLAZED PORCELAIN STONEWARE FLOOR TILE WITH COLORED TILE BODY, RECTIFIED.  
SOLS EN GRÈS CÉRAME EMAILLE COLORÉ DANS LA MASSE, RECTIFIÉ.  
GLASIERTE BODENFLIESE AUS DURCHGEFÄRBTEM FEINSTEINZEUG, REKTIFIZIERT.



**“Una trama densa di soluzioni mai scontate. Intrigante.”**

*Paul&Co*

**“A texture rich with unexpected twist. Intriguing.”**

**“Une trame pleine de solutions jamais données pour sur. Intrigant.”**

**“Eine Struktur reich an unerwarteten Lösungen. Intrigant.”**






Texture Cotton Naturale 60x60



Texture Cotton Lappato 30x60







**cotton**naturale











Texture Sand Lappato 60x60



Texture Sand Naturale 30x60





**sandlappato**



Texture Sand Lappato 60x60







Texture Canvas Naturale 60x60



Texture Canvas Lappato 30x60







**canvasnaturale**





Texture Canvas Naturale 60x60



**mokanaturale**






Texture Moka Lappato 60x60



Texture Moka Naturale 30x60







**mokalappato**





# Cotton



## Naturale




PTX 100 Texture Cotton Naturale 60x60 - 24"x24"




## Lappato



PTX 150 Texture Cotton Lappato 60x60 - 24"x24"



PTX 101 Texture Cotton Naturale 30x60 - 12"x24"



PTX 151 Texture Cotton Lappato 30x60 - 12"x24"

## Pezzi Speciali - Trims - Pièces spéciales - Sondertelle

Battiscopa - Skirting tiles - Plinthes - Sockelleisten



PTX 190 Battiscopa Texture Cotton Naturale 6,7x60 - 2,6"x24"

I battiscopa sono consegnati solo a scatole complete.  
The skirting tiles are supplied in full boxes only.  
Les plinthes ne sont livrées que par boîtes entières.  
Die Sockelleisten werden nur in ganzen Kartons abgegeben.





**Naturale**



PTX 200 Texture Sand Naturale 60x60 - 24"x24"



**Lappato**



PTX 250 Texture Sand Lappato 60x60 - 24"x24"



PTX 201 Texture Sand Naturale 30x60 - 12"x24"



PTX 251 Texture Sand Lappato 30x60 - 12"x24"

## Pezzi Speciali - Trims - Pièces spéciales - Sonderteile

Battiscopa - Skirting tiles - Plinthes - Sockelleisten



PTX 290 Battiscopa Texture Sand Naturale 6,7x60 - 2,6"x24"

I battiscopa sono consegnati solo a scatole complete.  
The skirting tiles are supplied in full boxes only.  
Les plinthes ne sont livrées que par boîtes entières.  
Die Sockelleisten werden nur in ganzen Kartons abgegeben.

# Canvas



**Naturale**



PTX 300 Texture Canvas Naturale 60x60 - 24"x24"



**Lappato**



PTX 350 Texture Canvas Lappato 60x60 - 24"x24"



PTX 301 Texture Canvas Naturale 30x60 - 12"x24"



PTX 351 Texture Canvas Lappato 30x60 - 12"x24"

## Pezzi Speciali - Trims - Pièces spéciales - Sonderteile

Battiscopa - Skirting tiles - Plinthes - Sockelleisten




PTX 390 Battiscopa Texture Canvas Naturale 6,7x60 - 2,6"x24"

I battiscopa sono consegnati solo a scatole complete.  
The skirting tiles are supplied in full boxes only.  
Les plinthes ne sont livrées que par boîtes entières.  
Die Sockelleisten werden nur in ganzen Kartons abgegeben.



**Naturale**




PTX 400 Texture Moka Naturale 60x60 - 24"x24"



**Lappato**



PTX 450 Texture Moka Lappato 60x60 - 24"x24"



PTX 401 Texture Moka Naturale 30x60 - 12"x24"



PTX 451 Texture Moka Lappato 30x60 - 12"x24"

## Pezzi Speciali - Trims - Pièces spéciales - Sondertelle

Battiscopa - Skirting tiles - Plinthes - Sockelleisten



PTX 490 Battiscopa Texture Moka Naturale 6,7x60 - 2,6"x24"

I battiscopa sono consegnati solo a scatole complete.  
The skirting tiles are supplied in full boxes only.  
Les plinthes ne sont livrées que par boîtes entières.  
Die Sockelleisten werden nur in ganzen Kartons abgegeben.



## CARATTERISTICHE TECNICHE - TECHNICAL FEATURES - CARACTERISTIQUES TECHNIQUES - TECHNISCHE EIGENSCHAFTEN

## PAVIMENTO IN GRES PORCELLANATO SMALTATO, COLORATO IN MASSA, RETTIFICATO - SPESSORE mm 10

GLAZED PORCELAIN STONEWARE FLOOR TILE WITH COLORED TILE BODY, RECTIFIED. - THICKNESS mm 10

SOLS EN GRÈS CÉRAME EMAILLE COLORÉ DANS LA MASSE, RECTIFIÉ. - ÉPAISSEUR mm 10

GLASIERTE BODENFLIESE AUS DURCHGEFÄRBTEN FEINSTEINZEUG, REKTIFIZIERT. - STÄRKE mm 10

## 60x60 - 30x60 - UNI EN14411 GRUPPO BIa GL APPENDICE G

|                                                                                                                                                                                                                                                 | VALORI PRESCRITTI<br>INTERNATIONAL STANDARD<br>VALEURS<br>INTERNATIONALE NORMIERTE | VALORI MEDI<br>AVERAGE VALUES<br>VALEURS MOYENS<br>MITTELWERT | NORMA<br>NORM<br>REGULATION<br>NORM |                                                                                                                                | VALORI PRESCRITTI<br>INTERNATIONAL STANDARD<br>VALEURS<br>INTERNATIONALE NORMIERTE | VALORI MEDI<br>AVERAGE VALUES<br>VALEURS MOYENS<br>MITTELWERT | NORMA<br>NORM<br>REGULATION<br>NORM |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------|-------------------------------------|
| LUNGHEZZA E LARGHEZZA<br>LENGTH AND WIDTH<br>LONGUEUR ET LARGEUR<br>LÄNGE UND BREITE DER FLIESEN                                                                                                                                                | ±0,6%                                                                              | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-2               | ASSORBIMENTO D'ACQUA<br>WATER ABSORPTION<br>ABSORPTION D'EAU<br>WASSERAUFNAHME                                                 | ≤ 0,5%                                                                             | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-3               |
| SPESSORE<br>THICKNESS<br>ÉPAISSEUR<br>STÄRKE                                                                                                                                                                                                    | ±5%                                                                                | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-2               | RESISTENZA ALLA FLESSIONE<br>BREAKING STRENGTH<br>RÉSISTANCE À LA FLEXION<br>BIEGEFESTIGKEIT                                   | ≥ 35 N/mm²                                                                         | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-4               |
| RETTILINEITÀ DEGLI SPIGOLI<br>STRAIGHTNESS OF CORNERS<br>EQUERRAGE DES ANGLES<br>GERADLINIGKEIT DER ECKEN                                                                                                                                       | ±0,5%                                                                              | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-2               | FORZA DI ROTTURA<br>BREAKING FORCE IN N<br>CHARGE DE RUPTURE<br>BRUCHLAST IN N                                                 | 1.300 N min                                                                        | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-4               |
| ORTOGONALITÀ<br>RECTANGULARITY<br>EQUERRAGE<br>RECHTWINKLIGKEIT                                                                                                                                                                                 | ±0,6%                                                                              | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-2               | RESISTENZA AGLI SBALZI TERMICI<br>THERMAL SHOCK RESISTANCE<br>RÉSISTANCE AU CHOCS THERMIQUES<br>TEMPERATURWECHSELBESTÄNDIGKEIT | RICHIESTA<br>REQUEST                                                               | RESISTENTE<br>RESISTANT<br>RESISTANT<br>BESTÄNDIG             | UNI EN ISO<br>10545-9               |
| PLANARITÀ<br>WARPAGE<br>PLANÉITÉ<br>EBENFLÄCHIGKEIT                                                                                                                                                                                             | ±0,5%                                                                              | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-2               | RESISTENZA AL GELO<br>FROST RESISTANCE<br>RÉSISTANCE AU GEL<br>FROSTBESTÄNDIGKEIT                                              | RICHIESTA<br>REQUEST                                                               | RESISTENTE<br>RESISTANT<br>RESISTANT<br>BESTÄNDIG             | UNI EN ISO<br>10545-12              |
| PEI RESISTENZA ALL'ABRASIONE SUPERFICIALE<br>PER PIASTRELLE SMALTATE<br>RESISTANCE TO SURFACE ABRASION<br>FOR GLAZED TILE<br>RÉSISTANCE À L'ABRASION DES SURFACE<br>DES CARREAUX EMAILLÉ<br>OBERFLÄCHENABRIEFESTIGKEIT<br>FÜR GLASIERTE FLIESEN | -                                                                                  | COTTON: 5<br>SAND: 5<br>CANVAS: 5<br><br>MOKA: 4              | UNI EN ISO<br>10545 - 7             | RESISTENZA ALL'ATTACCO CHIMICO<br>CHEMICAL RESISTANCE<br>RÉSISTANCE À L'ATTAQUE CHIMIQUE<br>CHEMISCHE BESTÄNDIGKEIT            | CLASSE UB min                                                                      | CONFORME<br>IN ACCORDANCE<br>CONFORME<br>ENTSPRECHEND         | UNI EN ISO<br>10545-13              |
|                                                                                                                                                                                                                                                 |                                                                                    |                                                               |                                     | RESISTENZA ALLE MACCHIE<br>STAIN RESISTANCE<br>RÉSISTANCE AUX TACHES<br>BESTÄNDIGKEIT GEGEN FLECKENBILDUNG                     | CLASSE 3 min                                                                       | CLASSE 4 min                                                  | UNI EN ISO<br>10545-14              |

## IMBALLI - PACKING - EMBALLAGES - VERPACKUNGSDATEN

| ARTICOLI              | PZ x BOX | MQ x BOX | KG x BOX | BOX x PAL | MQ x PAL | KG x PAL |
|-----------------------|----------|----------|----------|-----------|----------|----------|
| Fondo 60X60 Nat/Lapp  | 3        | 1,08     | 24,60    | 40        | 43,20    | 1004     |
| Fondo 30x60 Nat/Lapp  | 6        | 1,08     | 24,60    | 40        | 43,20    | 1004     |
| Battiscopa 6,7x60 Nat | 16       | -        | 18       | -         | -        | -        |

## Avviso ai signori posatori

Tutte le piastrelle devono essere esaminate prima della posa.

Non si accettano contestazioni dopo la posa in opera di materiale.

Posare il materiale attingendo da più scatole (almeno 5)

Fuga consigliata **MINIMO 2 mm**

## Notice

All tiles must be inspected prior to installation.

Complaints will not be accepted once the material has been laid.

Lay tiles by picking from several boxes (5 at least)

A joint of **MINIMUM 2 mm** is suggested

## Avis aux poseurs des carrelages

Les carreaux doivent être contrôlés avant la pose.

Une fois le matériel posé aucune réclamation sera acceptée.

Nous vous conseillons de poser cet article en prenant les carrelages dans plusieurs boîtes (au moins cinq).

Joint Conseillé **MINIMUM 2mm**

## Hinweis für die Fliesenleger

Alle Fliesen müssen vor der Verlegung geprüft werden.

Nach der Verlegung werden keine Reklamationen angenommen.

Das verlegte Material sollte aus mindestens 5 verschiedenen Kartons entnommen werden.

Empfohlene Fuge **MINDESTENS 2mm**

TEXTURE

Progettato e prodotto in Italia - Planned and produced in Italy

Projeté et produit en Italie. - In Italien geplant und produziert