

selce

Gres porcellanato/

porcelain tiles/grès cérame/Feinsteinzeug/ КЕРАМОГРАНИТ

Superficie/

surface/surface/ Oberfläche/ПОВЕРХНОСТИ

Opaca/ matt/matt/matt/МАТОВАЯ

selce: beige/bianco/grigio



cod. 0017221 Selce Beige MQ/136
33,5x33,5 - 13^{3/8}"x13^{3/8}" BOX/16





cod. 0017222 Selce Bianco MQ/136
33,5x33,5 - 13^{3/8}"x13^{3/8}" BOX/16



cod. 0017223 Selce Grigio MQ/136
33,5x33,5 - 13^{3/8}"x13^{3/8}" BOX/16

pezzi speciali

special trims / pieces speciales / sonderstücke / СПЕЦИАЛЬНЫЕ ЭЛЕМЕНТЫ

		 BATTISCOPA (coordinato) 8x33,5 - 3 ^{1/8} "x13,5" ML/39 BOX/32	 GRADINO LINEARE 33,5x33,5 - 13,5"x13,5" PZ/161 BOX/06	 GRADINO ANGOLARE 33,5x33,5 - 13,5"x13,5" PZ/180 BOX/02	 TORELLO PER GRADINO 5,5x33,5 - 2 ^{2/8} "x13,5" PZ/107 BOX/20
	Selce Beige	cod. 0017366	cod. 0018757	cod. 0018760	cod. 0017362
	Selce Bianco	cod. 0017367	cod. 0018758	cod. 0018761	cod. 0017363
	Selce Grigio	cod. 0017368	cod. 0018759	cod. 0018762	cod. 0017364
Battiscala DX e SX 8x34 - 3 ^{1/8} "x13 ^{3/8} " CP/138 BOX/20	Su richiesta del cliente è possibile realizzare il battiscala destro/sinistro / On request the step-skirting right/left is available on demand/ Sur demande du client il est possible de réaliser la plinthe de marche droite/gauche / Anfrage koennen Treppensockel links oder rechts koennen nach anfrage produziert werden / По запросу клиента могут быть произведены правые и левые подступенки				

Imballaggio/

packing / conditionnement / Verpackung / УПАКОВКА

Formato Size Format Format ФОРМАТ	Spessore Thickness Epaisseur Stärke ТОЛЩИНА	Pezzi/Sc Pcs/Box Pcs/Ctn Stck/Kart ШТ/КОР	m²/Sc m²/Box m²/Ctn m²/Kart КВ.М/КОР	kg/Sc kg/Box kg/Ctn kg/Kart КГ/КОР	Sc/Europal. Box Europal. Ctn/Europal Kart/Europal. КОР/ЕВРОПАЛ.	m²/Europal. m²/Europal. m²/Europal. m²/Europal. КВ.М/ЕВРОПАЛ.	kg/Europal. kg/Europal. kg/Europal. kg/Europal. КГ/ЕВРОПАЛ.
33,5x33,5	7,5	16	1,8	28	42	75,6	1176

Info tecniche/

technical info / info techniques / technische Info / ТЕХНИЧЕСКАЯ ИНФОРМАЦИЯ




INGELIVO



MOHS 7



PEI IV



mm 7,5



3 MIN



GA



≥ 35 N/mm²



≤ 0,5%